

### **TECHNICAL DATA SHEET**







Nijverheidslaan +50/56, B-8540 Deerlijk - BELGIUM Tel +32 56 617 977 - Fax +32 56 617 955 info@batterysupplies.be - www.batterysupplies.be



# TECHNICAL DATA SHEET

BAT/48325

### **APPLICATION**

Battery equalizer BAT/48325 is used for the 12V lead acid batteries which are connected in series to keep battery voltage balance and enhance battery life.

Battery equalizer can be used for 24V, 36V, 48V and any other N\*12V battery system.

1 piece for 24V system;

2 pieces for 36V system;

3 pieces for 48V system;

•••••

### **APPLICATION**

Battery nominal voltage	2*12V	
Optimizing current	0-5A	
Quiescent current	<3mA	
Dimensions	70*70*27 mm	
Protection	Reverse polarity protection	
Low Voltage Disconnect	10V	

### LED INDICATOR

	LED A	LED B
U(A)=U(B)	Off	Off
U(A)>U(B)	Flash	Off
U(A) < U(B)	Off	Flash
U(A)<10V	On	Off
U(B)<10V	Off	On
U(A/B)<10V	On	On



# **TECHNICAL DATA SHEET**


#### BAT/48325


#### **INSTALLATION**

Please connect the battery equalizer to battery as follows: (Please check the pictures)


- 1. Red cable: Battery B positive/+ pole
- 2. Black cable: Battery A negative/- pole

3. White cable: Battery B negative pole or Battery A positive pole. (The pole which connected Battery A and Battery B in series)






24V battery bank of 2 batteries



36V battery bank

24V battery bank of 4 batteries



48V battery bank

